

**IN THE CLAIMS**

This listing of the claim will replace all prior versions and listings of claim in the present application.

**Listing of Claims**

1. (currently amended) A method of migrating data from an old storage subsystem to a new storage subsystem in a data processing system which ~~comprises~~ includes a plurality of host computers and a plurality of storage subsystems; said method comprising the steps of:

conducting wherein there is provided a route-changing phase before migration of the data from the old storage subsystem to the new storage subsystem;

wherein, in said route-changing phase, sequentially changing an indication of access destination storage subsystems in said host computers such that an indication of the access destination storage subsystem of a first host computer is changed from said old storage subsystem to said new storage subsystem and then an indication of the access destination storage subsystem of a second host computer is changed from said old storage subsystem to said new storage subsystem after the access destination storage subsystem of the first host computer has been changed, thereby permitting each host computer to ~~can~~ access both the old and new storage subsystems, ~~and; and~~

in said route changing phase, by wherein said new storage subsystem, reads ~~reading~~ data from the ~~said~~ old storage subsystem in response to a read request from a host computer, ~~and send~~ sending the data to the ~~said~~ host

computer, and writing ~~writes~~ data into the said old storage subsystem in response to a write request from a host computer.

2. (currently amended) A method of migrating data according to claim 1, further comprising the step of:  
wherein by said new storage subsystem, ~~writes~~ writing data into said  
old storage subsystem in response to a write request from said host computer  
in said route-changing phase and ~~informs~~ informing said host computer of  
completion of said writing ~~the processing after ascertaining the data writing~~  
data writing processing has been completed.

3. (currently amended) A method of migrating data according to claim 1, wherein said new storage subsystem ~~reads~~ writing data ~~from~~ into said old storage subsystem in response to a ~~read~~ write request from said host computer and ~~sends the data to~~ informing said host computer write processing has been completed.

4. (currently amended) The method of migrating data according to claim 1, wherein a phase ~~before migration processing~~ is provided before said route-changing phase in which a route is set such that access from said host computer to said new storage subsystem is prohibited and access from said host computer to said old storage subsystem is allowed.

5. (original) A method of migrating data according to claim 1, wherein a data-migration phase is provided after said route-changing phase in

which a route is set such that access from said host computer to said old storage subsystem is prohibited and access to said new storage subsystem is allowed.

6. (currently amended) A method of migrating data according to claim 1, wherein, in ~~said a~~ data-migration phase, said new storage subsystem reads data from said new storage subsystem and sends the data to said host computer when the read request from said host computer is directed to a data-migration area, and  
wherein said new storage subsystem reads data from said old storage subsystem and sends the data to said host computer when the read request from said host computer is directed to a data-unmigrated area.

7. (currently amended) A method of migrating data according to claim 1, wherein a route is set such that access from said host computer to said old storage subsystem is prohibited and access to said new storage subsystem is allowed even after completion of ~~said a~~ data-migration phase.

8. (currently amended) A method of migrating data according to claim 1, wherein an access route to said new storage subsystem is set by at least one of ~~the manners~~ a plurality of method of changing a form of connection among said host computer, said old storage subsystem and said new storage subsystem,  
wherein said method further comprises:

using access restriction by a network connecting said host computer,  
said old storage subsystem and said new storage subsystem, and  
using access restriction by said storage subsystem.

9. (currently amended) A method of migrating data from an old storage subsystem to a new storage subsystem in a data processing system which includes a plurality of host computers and a plurality of storage subsystems said method comprising the steps of:

conducting a route-changing phase before migration of the data from the old storage subsystem to the new storage subsystem;

in said route-changing phase, permitting each host computer to access both the old and new storage subsystems;

in said route-changing phase, by said new storage subsystem, reading data from said old storage subsystem in response to a read request from a host computer, sending the data to said host computer, and writing data into said old storage subsystem in response to a write request from a host computer~~A method of migrating data according to claim 1,~~

wherein a route verification process is performed by which whether a route set in said route-changing phase is determined to be correct or not is verified~~is performed before migrating the data from said old storage subsystem to said new storage subsystem.~~

10. (currently amended) A method of migrating data according to claim 9, wherein a route is set such that access from said host computer to

said old storage subsystem is prohibited and access to said new storage

subsystem is allowed during said route verification process,

wherein said new storage subsystem writes data requested by said

host computer to said new storage subsystem and stores the-written data,

wherein said new storage subsystem, in response to a read request from said host computer, refers to said written data and checks to see if the data stored in said new storage subsystem during said route verification process are updated,

wherein when the data stored in said new storage subsystem are updated during said route verification process, the data are read from said new storage subsystem and sent to said host computer, and

wherein, when the data stored in said new storage subsystem are not updated during said route verification, the data are read from said old storage subsystem and sent to said host computer.

11. (currently amended) A method of migrating data according to claim 9, wherein ~~the data~~ updated during said route verification process are discarded when ~~an error is found in the set route~~ is determined to be incorrect during said route verification and the a state is returned to the onea state before the route change.

12. (currently amended) A method of migrating data according to claim 9, wherein ~~the data~~ updated during said route verification process are discarded when ~~an error is not found in the set route~~ is determined to be

~~correct~~during said route verification, and data-migration processing is executed after returning the ~~to a state to the one before the route change.~~

13. (currently amended) A method of migrating data from an old storage subsystem to a new storage subsystem in a data processing system which ~~comprises~~includes a plurality of host computers and a plurality of storage subsystems connected to said plurality of host computers; said method comprising the steps of:

~~wherein there is provided~~conducting a route-changing phase before migration of the data from the old storage subsystem to the new storage subsystem;

~~wherein,~~in said route-changing phase, sequentially changing an indication of access destination storage subsystems in said host computers such that an indication of the access destination storage subsystem of a first host computer is changed from said old storage subsystem to said new storage subsystem and then an indication of the access destination storage subsystem of a second host computer is changed from said old storage subsystem to said new storage subsystem after the access destination storage subsystem of the first host computer has been changed, thereby permitting said plurality of host computers to include ~~are~~route-changed host computers accessing said new storage subsystem and ~~route-unchanged~~ host computers accessing said old storage subsystem,

in said route changing phase, by ~~wherein~~said new storage subsystem, ~~reads~~reading data from said old storage subsystem in response to a read

request from said ~~a~~ route-changed host computer and ~~sends~~ sending the data to said route-changed host computer,

in said route changing phase, by ~~wherein~~ said new storage subsystem, ~~writes~~ writing data into said old storage subsystem in response to a write request from said route-changed host computer and ~~informs~~ informing said route changed host computer of completion of processing after ascertaining ~~the completion of~~ data-writing processing,

in said route changing phase, by ~~wherein~~ said old storage subsystem, ~~reading~~ reads data and ~~sends~~ sending the data to said ~~a~~ route changed host computer in response to a read request from said route-unchanged host computer, and

wherein in said route changing phase, by said old storage subsystem, ~~writing~~ writes data in response to a write request from said route-unchanged host computer and ~~informs~~ informing said route-changed host computer of completion of processing after ascertaining ~~the completion of~~ data-writing processing.